



**iiD 2 Secure**

# IID-TS200 Tripod Turnstile.

## TECHNICAL DATA

Size	420×330×1000mm
Housing material	SS304
Pass Speed	35 persons/min
Working temperature	-35°C-55°C
Gross weight	35KG/PCS
Passage width	510mm
Power supply	110-220V 50/60Hz
Motor voltage	DC24V
Working environment	Best for indoor
Working humidity	≤95% coagulation free
Open while power off	Yes
Working movement:	DC24V solenoid valve
LED light	direction arrow
Normal running life	3 million



## FEATURES

### Tripod turnstile function & Features

1. Alarm function: when arms are pushed by force illegally, alarm will be triggered automatically and arms will be set locked.
2. Turnstile can setting the working condition by press the button of main control board.
3. Auto-lift-arm function: the arm can lift automatically with alert when the power is on again.
4. Auto-drop-arm function: the arm can drop down automatically (default) (or free passing) when the power is off.
5. Automatic Reset Functions: after you swap the card, during the specific time (the system is 10s), if you didn't pass the turnstile, the system will cancel your authority automatically to pass the gate, (reset time is 1~60s you can adjust it what time is suit for you)
6. The turnstile can work with door access control system/ consumption system /biometric recognition system/ ESD system and so on
7. The turnstile is bidirectional (pedestrian can enter and exit from one set of turnstile)
8. LED indicator light
9. When pedestrian pass the turnstile, what should they do?
10. Once an open signal is given, the arms will rotate automatically to a 60 degree, and prompt the pedestrian to pass the gate.
11. Can manager the turnstile directly by managing the computer.
12. LED counting function

	Manual	Semi-Auto	Full-Auto
	×	√	√
	×	√	√
	NO action	manual- lift -arm	Auto-lift - arm
	NO action	Auto-drop- arm	Auto-drop- arm
	×	√	√
	×	√	√
	×	√	√
	manual push the arm	manual push the arm	Automatic- rotation
	×	√	√
	×	√	√
	×	√	√

Address: Heemstedestraat 16 Amsterdam, Netherlands

Phone Number: +31614762425 | E-mail: Info@iid2secure.nl | Website: www.iid2secure.nl