

Home » Products » Amplifiers » V-1000 Series Modular Amplifier » VP-1361 CE

Products Lineup

Audio System

[Amplifiers](#)
[Voice Evacuation System](#)
[PA Speakers](#)
[Pro-Audio Speakers](#)
[Wired Microphones](#)
[Wireless Microphones](#)
[Conference System](#)
[Network Audio Adapters](#)
[Intercom System](#)
[Megaphones](#)
[Audio Source Device](#)
[Rack-mount Equipment](#)
[Program Timer](#)
[Mixers](#)
[Audio Signal Processors](#)

CCTV System

Data Library

Here, TOA's Data Library equipped with a search engine offers its CAD drawings made out in pdf and dwg forms, EASE data, specification sheets, brochures, instruction and installation manuals, and a wealth of other product data for your downloading.



Download

VP-1361 Power Amplifier 360W (CE version)



VP-1361 CE

The VP-1361 power amplifier can be used for rack-mount application.



* 0 dB = 1 V

Specification


Power Source	AC: 220 - 230 V AC, 50/60 Hz DC: 24 V DC
Power Consumption	AC: 768 W (at rated output), 330 W (EN60065), 37 W (no-signal) DC: 20.9 A (at rated output), 0.5 A (no-signal)
Rated Output	360 W
Input	2 program inputs (parallel), 0 dB*, 20 kΩ, balanced 2 priority inputs (parallel), 0 dB*, 20 kΩ, balanced
Impedance	28 Ω (100 V)
S/N Ratio	80 dB or more
Total Harmonic Distortion	1 % or less (at rated output f = 1 kHz)
Frequency Response	80 Hz - 16 kHz, ±3 dB (at 1/3 rated output)
Ventilation	Fan cooling
Operating Temperature	0 °C to +40 °C (32 ° F to 104 ° F)
Operating Humidity	90 %RH or less (no condensation)
Finish	Panel: Aluminum, black, alumite
Dimensions	483.6 (W) × 132.6 (H) × 337.8 (D) mm (19.04" × 5.22" × 13.3")
Weight	16.6 kg (36.6 lb)
Accessory	Power cable (2 m (6.56 ft)) ...1, Removable terminal plug (2 pins) ...2, Removable terminal plug (3 pins) ...2, Removable terminal plug (5 pins) ...2, Fuse (6.3 A) ...1
Option	Fault detector: YA-1000A

What's new

IR topic



Investor Relations Top Interview



Sound tips: text version



Sound tips: video or animation version

Top of the Page