

Home » Products » Wired Microphones » Desktop Microphones » DM-524S

Products Lineup

Audio System

[Amplifiers](#)
[Voice Evacuation System](#)
[PA Speakers](#)
[Pro-Audio Speakers](#)
[Wired Microphones](#)
[Wireless Microphones](#)
[Conference System](#)
[Network Audio Adapters](#)
[Intercom System](#)
[Megaphones](#)
[Audio Source Device](#)
[Rack-mount Equipment](#)
[Program Timer](#)
[Mixers](#)
[Audio Signal Processors](#)

CCTV System

Data Library

Here, TOA's Data Library equipped with a search engine offers its CAD drawings made out in pdf and dwg forms, EASE data, specification sheets, brochures, instruction and installation manuals, and a wealth of other product data for your downloading.


[Download](#)

DM-524S Dynamic Microphone

DM-524S



A unidirectional microphone with a gooseneck shaft. Use this microphone in conjunction with the ST-73A desk-top stand (option).



Specification

Type	Moving coil microphone
Polar Pattern	Cardioid pattern
Rated Impedance	600 Ω, balanced
Rated Sensitivity	-54.5 dB (1 kHz, 0 dB=1 V/Pa)
Frequency Range	100 Hz - 10 kHz
Switch	Slide/short-off type
Output Connector	φ21, 3-pin plug (BTS21P3B)
Finish	Microphone body, Gooseneck shaft: Gold, sparkling paint
Weight	475 g
Usable Stand	ST-73A (option) or φ21 mm 3-pin socket
Accessories	φ21 3-pin receptacle (BTS21R3A).....1, M3×10 screw.....3, W3 washer.....3, SW3 spring washer.....3, M3 nut.....3

What's new

New Information



TOA expands its network audio adapter offerings.


[Contact Us](#)

A&E Specification Download


[Sound tips: text version](#)

[Sound tips: video or animation version](#)
[Top of the Page](#)