

Audio Sources

KB-F508R

The AP-F508R is an AM/FM stereo digital tuner that provides advanced technology and convenient use for a public address background music source. Main features are:

- Station memory stores up to 60 channels
- Manual/automatic tuning
- Fast channel scan
- Stereo/mono mode selection
- Color signal level&function LCD display
- Previous and next station selection
- RCA audio output jacks
- Attractive 1U rack mount case



SPECIFICATIONS	KB-F508R
Antenna Input	75 ohms
Audio Output	Better than 500 mV, 10k ohms
Frequency Response	20 Hz - 20 kHz (+/- 3dB)
S/N Ratio	AM: less than 40dB; FM: less than 45dB
THD	Less than 0.01% at 1kHz
Frequency Range	AM: 522 kHz-1620 kHz; FM: 87mHz-108mHz
Station Memory	60 Channels
Dimensions	51(H) x 483(W) x 255(D) mm

KB-DV

With original splendid fluorescence dynamic screen on aluminum panel, this AP-DV DVD player provides you super decoding solution and strong Disc correction function. Its main features are:

- Full functional infra-red leisurely remote controlling operation
- Support DVD, VCD, CD, HDCD, DIVX, SVCD, MPEG4, Mp3, WMA, CDR/RW format disc and auto play function
- Easy USB input and mono audio output
- With 19" rack mount bracket



SPECIFICATIONS	KB-DV
Antenna Input	1.5 V
Video Output	1VP-P
Frequency Response	20 Hz - 20 kHz
S/N Ratio	Better than 80dB
THD	Less than 0.01% at 1 kHz
Distortion and Noise	Less than -60dB at 1 kHz
Indicator	LCD display
Dimensions	65(H) x482 (W) x240 (D) mm

KB-MP3

- 128*64 LCD for easy control
- With built-in monitor speaker
- Support MP3/WMA/WAV format and 32 level volume control
- Removable USB storage up to 1GB
- Short Circuit timer signal to turn other units on/off
- Short Circuit alarm signal input to activate the recorded alarm message.
- 2 AC power output sockets up to 1000W, manual or auto timer control



SPECIFICATIONS	KB-MP3
Line in (REC)	10k ohm 330 mV, Unbalanced
Mic in (REC)	10k ohm ≤100 mV, Unbalanced
Line Out	10k ohm ≥300 mV, ±20 mV, Unbalanced
S/N Ratio	>75dB
File Format	Support MP3/WMA/WAV, Voice files
Volume adjust range	32 Level volume control (0 ~ 32)
Port	USB 1.1
Display	LCD display of menu
Power consumption	10 ~ 15 W
Dimensions	89(H) x483 (W) x382 (D) mm



REAR PANEL