



2MP PTZ Camera

APTD2I33



Key Features

- 1/2.9" SONY 2.1MP CMOS Sensor
- 3 IN 1 (AHD / HD- TVI / CVBS)
- 33x Optical zoom (IF=4.6mm-152mm Lens)
- IR Distance 120m max
- IP66 out door



www.iid2secure.nl
Extra Benefits, Less Price
Finestrat,19, 03530 La Nucua, Alicante, Spain
© IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands
Support@iid2secure.nl
+31614762425
Data Subject to change without notice



Specification

Model NO.	APTD2I33
Camera	
Image Sensor	1/2.9" SONY 2.1MP CMOS Sensor
image Resolution	2MP
TV System	PAL/NTSC
S/N Ratio	>50db
PTZ	
Horizontal Rotation Speed	120°/S
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	30°/s
Tilt Rotation Range	0°~93°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
Lens	
Focus Length	4.6mm-152mm
Focus Control	33X Optical Zoom
Night Vision	
Infrared LED	φ 42x6PCS IR LEDES + 2PCS Laser Lamp
IR Range	120m
Day-night mode	AUTO
Communication	
UTC	Support
RS485	Support
Interface	
Audio	/
Alarm	/
General	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non-Condensing
Power	DC12V/4A
Lightning Protection	Transient voltage 6000V
Size of Package (LxWxH)	31x31x44(cm)
Weight	10.7Kgs



www.iid2secure.nl
Extra Benefits, Less Price
Finestrat,19, 03530 La Nucua, Alicante, Spain
© IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands
Support@iid2secure.nl
+31614762425
Data Subject to change without notice

Dimensions

