

Home » Products » PA Speakers » Accessories » AT-303AP

Products Lineup

Audio System

[Amplifiers](#)
[Voice Evacuation System](#)
[PA Speakers](#)
[Pro-Audio Speakers](#)
[Wired Microphones](#)
[Wireless Microphones](#)
[Conference System](#)
[Network Audio Adapters](#)
[Intercom System](#)
[Megaphones](#)
[Audio Source Device](#)
[Rack-mount Equipment](#)
[Program Timer](#)
[Mixers](#)
[Audio Signal Processors](#)

CCTV System

Data Library

Here, TOA's Data Library equipped with a search engine offers its CAD drawings made out in pdf and dwg forms, EASE data, specification sheets, brochures, instruction and installation manuals, and a wealth of other product data for your downloading.

[Download](#)

AT-303AP Attenuator



AT-303AP

The AT-303AP is a flush-mounted wall attenuator and uses a transformer which allows connection of a wide range of loads (30 W or less). Volume can be adjusted in five steps. The AT-303AP features push-in terminal block for easy connection.



Specification

Input Range	0.5 W - 30 W
Attenuation	5 steps (0 dB, -6 dB, -12 dB, -18 dB, OFF)
Applicable Cable	600 V vinyl-insulated cable (Indoor Vinyl or Heat-resistant Indoor Vinyl cable) Solid cable: φ0.8 (0.03") - φ1.6 (0.06") mm
Terminal	Push-in connector
Operating Temperature	-10 °C to +50 °C
Finish	Knob, panel, plate: ABS resin, white (RAL 1013 equivalent) Case: ABS resin, black
Dimensions	70 (W) × 120 (H) × 52.4 (D) mm (2.76" × 4.72" × 2.06") (with plate) 41 (W) × 108 (H) × 52.4 (D) mm (1.61" × 4.25" × 2.06") (attenuator only)
Weight	210 g (0.46 lb) (unit only)
Accessory	Plate ...1, Plate mounting screw ...2, Box mounting screw ...2
Applicable Plate	YP-1AF (option)
Applicable Box	YS-11A (option)

Related Products

[YS-11A WALL MOUNTING BOX](#)
[YP-1AF Plate](#)

What's new

IR topic


[Investor Relations Top Interview](#)

[A&E Specification Download](#)

[Sound tips: text version](#)

[Sound tips: video or animation version](#)
[Top of the Page](#)