



BRAVO FD

Wireless Fire Detector

Description

BRAVO FD is a wireless combined fire detector (optical-smoke and heat detector) designed for operation in BRAVO wireless intruder alarm systems and with ECLIPSE WL wireless expander module in ECLIPSE hybrid systems. The detector is suitable for monitoring of 24-hour fire type zones and can be located in a distance up to 400m away from the control panel.



Technical Specifications

Battery 2x3V/1500mAh, CR123A type
Battery life 3 years
Operation frequency 868Mhz
Radio distance (open space) up to 400m
Operation temperature -10°C ÷ +50°C
Storing temperature -40°C ÷ +50°C
Sensitivity Rate-of-rise 10°C/min (max 60°C)
Class (according with EN54-5) A1R
Mounting height. up to 16m
Coverage area up to 120m²
Dimensions (including base) 103 x 56 mm

Functional Specifications

- Quick and easy mounting in the protected site
- Tamper switch for self-protection of the box
- Reset button for restoring the factory settings

Packing Information

- **Single packing box** - 1 unit BRAVO FD, dimensions 117 x 120 x 57mm
- **Master packing box** - 40 units BRAVO FD, dimensions 520 x 250 x 367mm

Compatible Product Range

- **BRAVO EXT** - Wireless panel with external power supply
- **BRAVO INTR** - Wireless panel with built-in power supply
- **ECLIPSE WL** - Wireless expander module for ECLIPSE control panels

Contact Information