



# BRAVO RC

## Key-fob Remote Control

### Description

BRAVO RC is a key-fob remote control designed for operation in BRAVO wireless intruder alarm systems or with ECLIPSE WL wireless expander module in ECLIPSE hybrid system. The User can quickly and easy arm and disarm the system, and in case of alarm events is announced with sound and LED indication from the key-fob.

Up to 8 remote key-fobs can be enrolled to one BRAVO panel.

Programmable (“Star”) and info (“i”) buttons for increased functionality.

BRAVO RC key-fob remote control is designed according the requirements and covers the standard EN50131, GRADE 2, Class II.



### Technical Specifications

Battery . . . . .	1x3V/600mAh, CR2450 type
Battery life . . . . .	3 years
Operation frequency . . . . .	868MHz
Radio distance (open space) . . . . .	up to 200m
Operation temperature . . . . .	-10°C ÷ +50°C
Storing temperature . . . . .	-40°C ÷ +50°C
Dimensions . . . . .	32 x 65 x 16 mm

### Functional Specifications

- Quick buttons for arm and disarm
- Programmable button (“Star”) for Stay arm, Siren Checking or Panic alarm
- Info button (“i”) for system status
- LED and sound indication for system status and memory alarm events and low battery on key fob

### Packing Information

- **Single packing box** - 1 unit BRAVO RC, dimensions 68 x 35 x 20 mm
- **Master packing box** - 440 units BRAVO RC, dimensions 496 x 305 x 206 mm

### Compatible Product Range

- **BRAVO EXT** - Wireless panel with external power supply
- **BRAVO INTR** - Wireless panel with built-in power supply
- **ECLIPSE WL** - Wireless expander module for ECLIPSE control panels

### Contact Information