



## CA 62 Alarm Control Panel

### Description

CA 62 is up to 12 zone alarm control panel with 2 partitions, appropriate for security of homes, medium sized commercial premises and offices.

The panel can be managed by means of: a keypad - LED or LCD; a proximity cards reader; a remote controls, or remote programming software. Programming is done via keypad or programming software ProsTE. CA 62 has a built in digital communicator for sending alarm messages to monitoring station.

The panel is available in plastic or metal box.

### Technical Specifications

Mains Supply Voltage . . . . . 230V  $\pm$  10%  
Mains Transformer . . . . . 17VAC / 17 VA  
Back-up Battery . . . . . 12V / 7 Ah  
Battery Charger . . . . . 13.8 V / 1A, Resettable fuse protected  
Current consumption . . . . . 100 mA  
Power output . . . . . 13.8 V DC / 1 A, Resettable fuse protected  
Keypads . . . . . up to 4 (LED and LCD)  
Proximity readers . . . . . up to 2  
Operating Temperature . . . . . 0°C / +50°C  
Dimensions, plastic box . . . . 335 x 290 x 105 mm  
Dimensions, metal box . . . . 318 x 258 x 75 mm



### Functional Specifications

Zones . . . . . up to 12; 5 on board (10 using doubling zone) + 2 keyboard zones  
Balancing of zones . . . . . 1 or 2 balancing resistors; doubling zone connection  
Partitions . . . . . 2  
Outputs . . . . . 3 low current + 1 high current  
Access Codes . . . . . 20 user, 4 manager, 1 engineering  
Memory LOG . . . . . 256 events with date and time  
Digital Communicator . . . . . 2 telephone numbers; built in; CIA and Contact ID protocols

### Packing Information

- **Master box, plastic box** - 5 units CA62, dimensions 560 x 362 x 320 mm
- **Master box, metal box** - 5 units CA62, dimensions 448 x 350 x 285 mm

### Compatible Product Range

- **LED 62** - keypad
- **LCD 64** - keypad
- **PR 62** - proximity reader
- **VD60** - voice dialer
- **TITAN series** - PIR detectors
- **SR 105; SR110** - indoor sirens
- **SR 200; SR300** - outdoor sirens
- **MDU 2; MDU V** - remote control modules
- **SensoMAG INTR** - fire detectors with relay base 12V
- **GBD10, GBD20** - glass break detectors
- **AUMS-12S** - magnetic contacts
- **ARGUS** - Universal GSM communication module
- **AJAX LAN** - Universal LAN communication module
- **AJAX GSM/GPRS** - Universal GSM/GPRS communication module
- **AJAX SP** - WEB application for monitoring and control
- **ProsTE** - Specialized programming software

### Contact Information