

www.black.honeywell.com

1 SATA 4-/8-/16-Channel High Resolution Network Video Recorder

Honeywell Black™ CALNVR-1004/08/16A series is an easy to use network recording solution designed for small-scale surveillance application. Featuring 3 Megapixel / 1080P / 960P outstanding real-time recording resolution, 1080P HDMI & VGA output, H.264 video compression, and compatibility with 1.3 Megapixel IP cameras, this NVR series optimizes recording quality to provide outstanding video performance at an economical price.

The user-friendly operation interface with button panel allows users to live view, record, playback, back up and remotely control the system simultaneously. With 1 SATA slot, the maximum storage capacity of the CALNVR-1004/08/16A is up to 4TB.

The CALNVRView mobile view APP allows a quick remote access and control to CALNVR-1004/08/16A via your mobile phone. Free DDNS server service is available to support remote control of the NVR. The CALNVR-1004/08/16A also comes with a free CMS software CAL-CMS200 which provides rich functions such as video management, user management, storage, video output, etc.

Market Opportunities

Featuring real-time recording up to 3 Megapixel / 1080P / 960P resolution, the CALNVR-1004/08/16A series is an ideal solution for high definition surveillance. This easy-to-configure and easy-to-operate NVR series is ideal for small-scale surveillance installations such as in retail stores, dispensaries, clinics, offices or hotels.

FEATURES

- Button-panel interface for easy operation
- Multiplex recording schedule options: manual, alarm, motion detection, timing
- Multiplex operation: live view, record, play back, backup and remotely control the system simultaneously
- HDMI and VGA output simultaneously at up to 1080P resolution
- H.264 High profile decoding
- 1 SATA HDD interface: maximum 4TB storage capacity
- ONVIF 2.0 compliant
- Support remote control through DDNS service by free of charge
- On-line user view: maximum 6 users simultaneously
- CALNVRView: free Android and Apple app for remote playback, record and snapshot through mobile phone
- Multiple network monitoring: CAL-CMS200 (for PC), CALNVRView (for mobile app), IE Web browser
- Power: DC12V







www.black.honeywell.com

1 SATA 4-/8-/16-Channel High Resolution Network Video Recorder

SPECIFICATIONS

		CALNVR-1004A	CALNVR-1008A	CALNVR-1016A	
	Operating System	Embedded LINUX		`	
System	System Resources	Simultaneous multi-channel live view, real-time recording, playback, network operatio access, backup			
Interface	User Interface	Support 16-bit true color graphical menu interface and mouse operation			
	Preview Screen	1 / 4 Windows	1/4/9 (8 channels) Windows	1 / 4 / 9 (8 channels) / 16 Windows	
Video	IP Video Input	4 channels	8 channels	16 channels	
	Video Standards	PAL (625 line, 50f/s), NTSC (525 line, 60f/s)			
	Video Compression	H.264 High profile, main profile, baseline			
	Display Quality	Monitor: D1 & VGA & HDMI: HD		VGA & HDMI: HD	
	Play Quality	960P / 720P / 960H / D1 / HD1 / CIF / QCIF	1080P / 720P / 960H / D1 / HD1 / CIF / QCIF	3 Megapixel / 1080P / 720P	
	Video Access	4 channels 720P / 8 channels D1	8 channels 1080P / 8 channels 720P / 16 channels D1	4 channels 3 Megapixel / 8 channels 1080P / 16 channels 960P (720P)	
	Motion Detection	Support			
Audio Record & Playback	Audio Compression	G.711A			
	Bidirectional Talk	N/A		Support	
	Record Mode	Manual / Alarm / Video Detection / Timing			
	Local Playback	1 channel 960P (720P) / 4 channels D1 real-time	2 channels 1080P (960P) / 4 channels 720P real-time	1 channel 3M / 2 channels 1080P / 4 channel 720P real-time	
	Search Mode	Time / Calendar / Event / Char			
	HDD Redundancy	Support			
Storage & Backup	Space Occupation	Video: 1080P 80G / Day / Channel, 720P 26G / Day / Channel, 960H 24G / Day / Channel, D1 16~20G / Day / Channel, Audio: 691.2M / Day / Channel			
	Record Storage	HDD, network			
	Backup Mode	Network backup, USB HDD, USB writer, SATA writer			
	Video Input	RJ45			
		1 channel BNC output, 1 channel VGA output, 1 channel HDMI output		T T T T T T T T T T T T T T T T T T T	
	Video Output		nel VGA output, 1 channel HDMI	1 channel VGA output, 1 channel HDMI output	
	Video Output Audio Input		nel VGA output, 1 channel HDMI	1	
	·	output	nel VGA output, 1 channel HDMI	channel HDMI output	
Interface	Audio Input	output N/A	nel VGA output, 1 channel HDMI	channel HDMI output	
Interface	Audio Input Audio Output	output N/A 1 channel RCA	nel VGA output, 1 channel HDMI	channel HDMI output	
Interface	Audio Input Audio Output Alarm Input	output N/A 1 channel RCA N/A	nel VGA output, 1 channel HDMI	channel HDMI output 1 channel RCA	
Interface	Audio Input Audio Output Alarm Input Alarm Output	output N/A 1 channel RCA N/A N/A		channel HDMI output 1 channel RCA	
Interface	Audio Input Audio Output Alarm Input Alarm Output Net Interface	output N/A 1 channel RCA N/A N/A 1 RJ-45 10M / 100M 1 RS485, support 18 kinds of		channel HDMI output 1 channel RCA 1 RJ45 10M / 100M / 1000M	
Interface	Audio Input Audio Output Alarm Input Alarm Output Net Interface PTZ Control	output N/A 1 channel RCA N/A N/A 1 RJ-45 10M / 100M 1 RS485, support 18 kinds of	PTZ protocols	channel HDMI output 1 channel RCA 1 RJ45 10M / 100M / 1000M	
Interface	Audio Input Audio Output Alarm Input Alarm Output Net Interface PTZ Control USB Port HDD Interface	output N/A 1 channel RCA N/A N/A 1 RJ-45 10M / 100M 1 RS485, support 18 kinds of 12 USB 2.0 port for mouse, back	PTZ protocols	channel HDMI output 1 channel RCA 1 RJ45 10M / 100M / 1000M	
Interface	Audio Input Audio Output Alarm Input Alarm Output Net Interface PTZ Control USB Port	output N/A 1 channel RCA N/A N/A 1 RJ-45 10M / 100M 1 RS485, support 18 kinds of 12 USB 2.0 port for mouse, bace 1 SATA, max 4TB	PTZ protocols	channel HDMI output 1 channel RCA 1 RJ45 10M / 100M / 1000M	
	Audio Input Audio Output Alarm Input Alarm Output Net Interface PTZ Control USB Port HDD Interface Power Supply	output N/A 1 channel RCA N/A N/A 1 RJ-45 10M / 100M 1 RS485, support 18 kinds of 12 USB 2.0 port for mouse, bace 1 SATA, max 4TB 12V / 2A	PTZ protocols	channel HDMI output 1 channel RCA 1 RJ45 10M / 100M / 1000M	
Interface General	Audio Input Audio Output Alarm Input Alarm Output Net Interface PTZ Control USB Port HDD Interface Power Supply Power Consumption Operating	output N/A 1 channel RCA N/A N/A 1 RJ-45 10M / 100M 1 RS485, support 18 kinds of 12 USB 2.0 port for mouse, bac 1 SATA, max 4TB 12V / 2A Max. 15W	PTZ protocols	channel HDMI output 1 channel RCA 1 RJ45 10M / 100M / 1000M	
	Audio Input Audio Output Alarm Input Alarm Output Net Interface PTZ Control USB Port HDD Interface Power Supply Power Consumption Operating Temperature	output N/A 1 channel RCA N/A N/A 1 RJ-45 10M / 100M 1 RS485, support 18 kinds of 12 USB 2.0 port for mouse, bace 1 SATA, max 4TB 12V / 2A Max. 15W 0°C - +55°C	PTZ protocols	channel HDMI output 1 channel RCA 1 RJ45 10M / 100M / 1000M	
General	Audio Input Audio Output Alarm Input Alarm Output Net Interface PTZ Control USB Port HDD Interface Power Supply Power Consumption Operating Temperature Operating Humidity	output N/A 1 channel RCA N/A N/A 1 RJ-45 10M / 100M 1 RS485, support 18 kinds of 12 USB 2.0 port for mouse, bace 1 SATA, max 4TB 12V / 2A Max. 15W 0°C - +55°C 10%-90%	PTZ protocols	channel HDMI output 1 channel RCA 1 RJ45 10M / 100M / 1000M	
	Audio Input Audio Output Alarm Input Alarm Output Net Interface PTZ Control USB Port HDD Interface Power Supply Power Consumption Operating Temperature Operating Humidity	output N/A 1 channel RCA N/A N/A 1 RJ-45 10M / 100M 1 RS485, support 18 kinds of 1 2 USB 2.0 port for mouse, bac 1 SATA, max 4TB 12V / 2A Max. 15W 0°C - +55°C 10%-90% 255 (W) x 225 (D) x 45 (H) mm	PTZ protocols	channel HDMI output 1 channel RCA 1 RJ45 10M / 100M / 1000M	
General	Audio Input Audio Output Alarm Input Alarm Output Net Interface PTZ Control USB Port HDD Interface Power Supply Power Consumption Operating Temperature Operating Humidity Dimensions	output N/A 1 channel RCA N/A N/A 1 RJ-45 10M / 100M 1 RS485, support 18 kinds of 12 USB 2.0 port for mouse, bace 1 SATA, max 4TB 12V / 2A Max. 15W 0°C - +55°C 10%-90% 255 (W) x 225 (D) x 45 (H) mm ONVIF 2.0	PTZ protocols ekup, DVD burning and upgrading	channel HDMI output 1 channel RCA 1 RJ45 10M / 100M / 1000M	

Note: Honeywell reserves the right, without notification, to make changes in product design or specifications.




www.black.honeywell.com

1 SATA 4-/8-/16-Channel High Resolution Network Video Recorder

DIMENSION

FRONT PANEL:



Unit (mm)

REAR PANEL:



CALNVR-1004/1008A



CALNVR-1016A

ORDERING

CALNVR-1004A	4-channel 720P / 8-channel D1 NVR, 1 HDD SATA, max 4TB, DC12V, ONVIF
CALNVR-1008A	8-channel 1080P / 8-channel 720P / 16-channel D1 NVR, 1 HDD SATA, max 4TB, DC12V, ONVIF
CALNVR-1016A	4-channel 3 Megapixel / 8-channel 1080P / 16-channel 960P (720P) NVR, 1 HDD SATA, max 4TB, DC12V, ONVIF

PACKAGE


Qty	Components
1	CALNVR-1004A/08A/16A NVR
1	Power Adapter
1	Warranty Card
1	Software CD
1	USB Mouse
1	Install Screws
1	Remote Controller
1	User Manual



www.black.honeywell.com

1 SATA 4-/8-/16-Channel High Resolution Network Video Recorder

SYESTEM DIAGRAM



For more information:

Security East Asia

Security Pacific

Security India Security Middle East & N.Africa

Security Russia Security China

Security Korea

www.black.honeywell.com security.black@honeywell.com

Honeywell Security Group Automation & Control Solution

Automation & Control Solutions Honeywell International Inc. www.security.honeywell.com Tel: (852) 2405 2323

Tel: 1300 234 234

Tel: (91) 124 4975000

Tel: (971) 4454 1704

Tel: (7) 495 7979371

Tel: (86) 400 8800 330





July 2014 © 2014 Honeywell International Inc.