

Home » Products » Wired Microphones » Handheld Microphones » DM-1200

Products Lineup

Audio System

- [Amplifiers](#)
- [Voice Evacuation System](#)
- [PA Speakers](#)
- [Pro-Audio Speakers](#)
- [Wired Microphones](#)
- [Wireless Microphones](#)
- [Conference System](#)
- [Network Audio Adapters](#)
- [Intercom System](#)
- [Megaphones](#)
- [Audio Source Device](#)
- [Rack-mount Equipment](#)
- [Program Timer](#)
- [Mixers](#)
- [Audio Signal Processors](#)

CCTV System

Data Library

Here, TOA's Data Library equipped with a search engine offers its CAD drawings made out in pdf and dwg forms, EASE data, specification sheets, brochures, instruction and installation manuals, and a wealth of other product data for your downloading.



DM-1200 Unidirectional Microphone



DM-1200

The DM-1200 microphone is designed for speech applications and features high intelligibility.

Specification


Type	Moving coil microphone
Directivity	Unidirectional
Rated Impedance	600 Ω, balanced
Rated Sensitivity	-52 dB (1 kHz 0 dB=1 V/Pa)
Frequency Response	50 - 12,000 Hz
Connection Cable	Single-core shielded cable, unbalanced
Cable Length	10 m
Terminal of Cable	Phone plug
Talk Switch	Short-off, slide switch
Finish	Body: Die-cast zinc, metallic gray Head: Die-cast aluminum/zinc-plated steel wire, metallic gray
Dimensions	φ39.5 × 163 mm (microphone body)
Weight	265 g (without connection cable)
Accessory	Microphone holder (W5/16 , W5/8 , W3/8)...1



What's new

New Information

TOA expands its network audio adapter offerings.



Sound tips: text version



Sound tips: video or animation version

[Top of the Page](#)