

DM-3400

Order No. 23.6340

Dynamic microphone, for stage, speech and vocals.

- Cardioid polar pattern
- Diecast metal body
- Supplied with microphone holder, cable and plastic case

Model	DM-3400
Polar pattern	cardioid
System	dynamic
Audio frequency range	50-15,000 Hz
Nominal impedance	600 Ω
Sensitivity	2.5 mV/Pa
Max. sound pressure	140 dB
Housing material	diecast metal
Dimensions	Ø 45 mm x 180 mm
Weight	610 g
Cable	5 m, low-noise, XLR, bal.
Connection	XLR, bal.



DM-1800

Order No. 23.6330

Dynamic microphone, for stage, speech and vocals.

- Cardioid polar pattern
- Diecast metal body
- Supplied with microphone holder and cable

Model	DM-1800
Polar pattern	cardioid
System	dynamic
Audio frequency range	60-14,000 Hz
Nominal impedance	630 Ω
Sensitivity	2.8 mV/Pa
Max. sound pressure	140 dB
Housing material	diecast metal
Dimensions	Ø 46 mm x 170 mm
Weight	600 g
Cable	5 m, low-noise, XLR, bal.
Connection	XLR, bal.



DM-1500

Order No. 23.6750

Dynamic microphone, for general applications.

- Cardioid polar pattern
- High-gloss aluminium version, black chromium-plated
- On/off switch

Model	DM-1500
Polar pattern	cardioid
System	dynamic
Audio frequency range	80-12,000 Hz
Nominal impedance	600 Ω
Sensitivity	1.8 mV/Pa
Max. sound pressure	140 dB
Housing material	aluminium
Dimensions	Ø 45 mm x 165 mm
Weight	274 g
Cable	3 m, low-noise, 6.3 mm plug
Connection	XLR, bal.



DM-800

Order No. 23.6320

Dynamic microphone, for general applications.

- Cardioid polar pattern
- Plastic version
- Supplied with microphone holder and cable

Model	DM-800
Polar pattern	cardioid
System	dynamic
Audio frequency range	80-12,000 Hz
Nominal impedance	600 Ω
Sensitivity	2.5 mV/Pa
Max. sound pressure	125 dB
Housing material	plastic
Dimensions	Ø 56 mm x 170 mm
Weight	350 g
Cable	3 m, low-noise, 6.3 mm plug
Connection	XLR, bal.

