



- COMPANY +
- NEWS +
- PRODUCTS +
- LOGIN +
- INQUIRE +
- DOWNLOAD +
- SUPPORT +

- PRODUCTS ▾
- Network Camera
- NVR system
- Activa Flex
- POE
- Activa Pro
- Alarm System
- Activa
- HD-AHD
- AHD/TVI/CVI/906H 4-in-1 camera
- DiskRAID
- HD-CVI
- Mobile Solution
- Twisted Pair & Fiber parking system solution
- Access Control
- Accessories

## FAE-50/100/150/200/250 Outdoor/Indoor 3 Photoelectric Beams



Specification	Dimension	Accessories	Download	Video		
Model		FAE-50	FAE-100	FAE-150	FAE-200	FAE-250
Recommended Protection Distance	Outdoor	50m	100m	150m	200m	250m
	Indoor	150m	300m	450m	600m	750m
Max.Arrival Distance		450m	900m	1350m	1800m	2250m
Infrared Beam	3 beams					
Detection System	Simultaneous Cut-off of 3 Beams					
Light Source	Pulsed Infrared					
Response Time	50-700ms					
Alarm Output	Relay On/Off output, Rating:AC/DC30V 500mA max					
Power Supply	13.8-24VDC or 11-18VAC					
Current Consumption	TX	60mA	60mA	60mA	60mA	60mA
	RX					
Working Temperature	-25°C - 55°C					
Tamper Output	NC Contact, Rating:24Vdc/500mA max.					
Optical Axis Adjustable Angle (Horizontal)	180° (±90°)					
Optical Axis Adjustable Angle (Vertical)	20° (±10°)					
Mcssurc for Moisturc/Frost/Dcw	Heating Covcr (Optional)					
Material	Polycarbonate (PC)					
Weight	1.5Kg					
Remarks	Black color					

- < GO BACK
- PRINT
- JOIN INQUIRE >

12F.,No.103,Sec.3, Nanjing East Road, Taipei , Taiwan, R.O.C. dressing <http://www.fashionreplicawatches.co.uk/> Tel:886-2-2506-6788 / Fax: 886-2-2506-8887  
<http://www.winwatches.co.uk/category/rolex-replica/> / E-mail: [sales@finecctv.com](mailto:sales@finecctv.com)  
 Copyright © 2018 FINEST SECURITY SYSTEM Co., LTD. All Rights Reserved.