



- COMPANY +
- NEWS +
- PRODUCTS +
- LOGIN +
- INQUIRE +
- DOWNLOAD +
- SUPPORT +

- PRODUCTS ▾
- Network Camera
- NVR system
- Activa Flex
- POE
- Activa Pro
- Alarm System
- Activa
- HD-AHD
- AHD/TVI/CVI/906H 4-in-1 camera
- DiskRAID
- HD-CVI
- Mobile Solution
- Twisted Pair & Fiber parking system solution
- Access Control
- Accessories

FAH-50/100/150/200/250

Outdoor/Indoor 4 Photoelectric Beams



Specification
Dimension
Accessories
Download
Video

Model		FAH-50	FAH-100	FAH-150	FAH-200	FAH-250
Recommended Protection Distance	Outdoor	50m	100m	150m	200m	250m
	Indoor	150m	300m	450m	600m	750m
Max.Arrival Distance		450m	900m	1350m	1800m	2250m
Infrared Beam		4 beams				
Detection System		Simultaneous Cut-off of 4 Beams				
Light Source		Pulsed Infrared				
Response Time		35-700ms				
Alarm Output		Relay On/Off output, Rating:AC/DC30V 500mA max				
Power Supply		13.8-24VDC or 11-18VAC				
Current Consumption	TX	95mA	100mA	100mA	100mA	105mA
	RX					
Working Temperature		-25°C - 55°C				
Tamper Output		NC Contact, Rating:24Vdc/500mA max.				
Optical Axis Adjustable Angle (Horizontal)		180° (±90°)				
Optical Axis Adjustable Angle (Vertical)		20° (±10°)				
Mcssurc for Moisturc/Frost/Dcw		Heating Covcr (Optional)				
Material		Polycarbonate (PC)				
Weight		2.0Kg				
Remarks		Black color				

< GO BACK
PRINT
JOIN INQUIRE >

12F.,No.103,Sec.3, Nanjing East Road, Taipei , Taiwan, R.O.C. dressing <http://www.fashionreplicawatches.co.uk/> Tel:886-2-2506-6788 / Fax: 886-2-2506-8887
<http://www.winwatches.co.uk/category/rolex-replica/> / E-mail: sales@finecctv.com
 Copyright © 2018 FINEST SECURITY SYSTEM Co., LTD. All Rights Reserved.