



- COMPANY +
- NEWS +
- PRODUCTS +
- LOGIN +
- INQUIRE +
- DOWNLOAD +
- SUPPORT +

- PRODUCTS ▾
- Network Camera
- NVR system
- Activa Flex
- POE
- Activa Pro
- Alarm System
- Activa
- HD-AHD
- AHD/TVI/CVI/906H 4-in-1 camera
- DiskRAID
- HD-CVI
- Mobile Solution
- Twisted Pair & Fiber
- parking system solution
- Access Control
- Accessories

FAP-20/30/40/60/80/100

Outdoor/Indoor Dual Photoelectric Beams



- Specification
- Dimension
- Accessories
- Download
- Video

Model	FAP-20	FAP-30	FAP-40	FAP-60	FAP-80	FAP-100
Recommended Protection Distance	Outdoor	20m	30m	40m	60m	100m
	Indoor	60m	90m	120m	180m	300m
Max.Arrival Distance	200m	350m	450m	650m	900m	1100m
Infrared Beam	2 beams					
Detection System	Simultaneous Cut-off of 2 Beams					
Light Source	Pulsed Infrared					
Response Time	50-700ms, Adjustable					
Alarm Output	Relay On/Off output, Rating:AC/DC30V 500mA max					
Power Supply	13.8-24VDC or 11-18VAC					
Current Consumption	TX	40mA	40mA	55mA	55mA	65mA
	RX					65mA
Working Temperature	-25°C - 55°C					
Tamper Output	NC Contact, Rating:24Vdc/500mA max.					
Optical Axis Adjustable Angle (Horizontal)	180° (±90°)					
Optical Axis Adjustable Angle (Vertical)	20° (±10°)					
Mcassurc for Moisturc/Frost/Dcw	Hcating Covcr (Optional)					
Material	Polycarbonate (PC)					
Weight	1.0Kg					
Remarks	Black color					

- < GO BACK
- PRINT
- JOIN INQUIRE >

12F.,No.103,Sec.3, Nanjing East Road, Taipei , Taiwan, R.O.C. dressing <http://www.fashionreplicawatches.co.uk/> Tel:886-2-2506-6788 / Fax: 886-2-2506-8887
<http://www.winwatches.co.uk/category/rolex-replica/> / E-mail: sales@finecctv.com
 Copyright © 2018 FINEST SECURITY SYSTEM Co., LTD. All Rights Reserved.