


Model:		<ul style="list-style-type: none"> * 1080P Video camera X 1 * 4.3"LCD Receiver X 1 * DC 5V 1.5A Power adapter X2 * 1 m power cord X2 * User Manual X1 * Screw bag X1 	
<div style="border: 1px solid black; border-radius: 10px; padding: 5px; display: inline-block; background-color: #00A0C0; color: white; font-weight: bold;">HW-BB200M</div>			
Packing box size(mm)/weight(kg)		1pcs : 195*174*65 mm ; 0.42KG	
Outer box size(mm)/weight(kg)		30pcs/box : 410*350*540 mm ; 15.4 KG	
Specification parameter			
project		parameter	
Transmission frequency		WIFI 2.4GHz	
antenna		Built-in concealment	
transmission distance		300m (Barrier free)	
working temperature		-10°C~ +50°C/ +14 ~ +122F	
Storage temperature		-20°C~ +60°C/ -4 ~ +140F	
Working humidity		85%RH	
Video camera	Main Chip	XM530AI,Dual-core 32-bit DSP	
	sensor	SC2235E 1/3" Progressive Scan Sensor	
	Image Pixel	MAX 1920*1080	
	Low illumination	Color: 0.1Lux@F1.2; B/W: 0.01Lux@F1.2	
	Consumption	<3W	
	Power Supply	DC 5V 1.5A	
	size	61*62*117 mm	
	Weight	0.08 kg	
Receiver	Main Chip	XM630FX ,Dual-core 32-bit DSP	
	Material of LCD Screen	TFT	
	LCD screen size	4.3"	
	Resolution	600*320	
	effective area	95.04mm(W)×53.856mm(H)	
	Pixel spacing	0.198mm(H)×0.198mm(W)	
	Built-in lithium battery	2000 mAh	
	Duration of endurance	5 hours	
	Power Supply	DC 5V 1.5A	
	size	156*86*16 mm	
	Weight	0.12 kg	