S4A INDUSTRIAL CO.,LIMITED















Specifications

Material	aluminum
color	grey
unlock method	Face, Pincode, Key, MF1, Fingerprint, USB Emergency PS
Quiescent Current	50 microphones
Working current	300mAh (capacity)
Open face ability	<= 100
Fingerprint opening ability	<= 100
Password to open capacity	<= 5
Open card capacity	<= 20
camera	Infrared and Color Cameras
Start Time	<1 second
Far	0.00%
Far FRR	0.00% 0.01%
FRR	0.01%
FRR speed perception	0.01% 0.5 seconds
FRR speed perception Operating Voltage	0.01%0.5 seconds8.4V lithium battery power supply (not included)
FRR speed perception Operating Voltage Low Wattage Alarm	0.01%0.5 seconds8.4V lithium battery power supply (not included)6.8V
speed perception Operating Voltage Low Wattage Alarm Emergency Power Supply	0.01% 0.5 seconds 8.4V lithium battery power supply (not included) 6.8V 5V/2A (power bank available)
speed perception Operating Voltage Low Wattage Alarm Emergency Power Supply current consumption	0.01% 0.5 seconds 8.4V lithium battery power supply (not included) 6.8V 5V/2A (power bank available) Static <30µm
speed perception Operating Voltage Low Wattage Alarm Emergency Power Supply current consumption specified distance	0.01% 0.5 seconds 8.4V lithium battery power supply (not included) 6.8V 5V/2A (power bank available) Static <30µm 30-80 cm.

