



# IID-DB3I25MN

3.0M star-light illumination H.265  
Intelligent analysis Network Camera

## Key Features:

- 3.0M star-light illumination HD resolution, clear and fine images, Auto focal
- Support multiple intelligent analysis
- Support 2D/3D noise reduction, digital wide dynamic
- Advanced H.265/H.264 video compression, Super low rate, high definition quality of image
- Professional anti-lightning, conform to GB/T17626.5 and IEC61000-4-5
- Support ONVIF, access third party
- Support various mobile monitoring (iPhone, Android);
- Provide web, CMS center platform management software MYEYE provide SDK development
- Support cloud technology, easy to achieve network penetration, from in-line and alarm information pushed



Model	IID-DB3I25MN
System structure	Embedded RTOS dual-core 32bit DSP(Hi3516CV300),pure hard compression ,watch dog
Sensor	3.0M 1/2.8" IMX291 star-light illumination CMOS sensor ,color 0.0001Lux@F1.2,black/white 0.0001Lux@F1.2
Video compression	H.265/H.264,support dual stream,AVI;0.1M~8Mbps variable;1~30f/s variable
Image output	Main stream: 1920*1080@25fps, 1280*720@25fps; sub-stream: 704*576@25fps;
Shutter	1/50(1/60)s to 1/10,000s
Lens	4mm F1.0 professional black light lens
IR Distance	25m
IR LED	N/A
Day and night	Support IR-CUT
Noise reduction	Support 2D/3D
Wide dynamic	True, not less than 120dB
ONVIF	Support
Mobile monitoring	Support multiple mobile monitoring ( iOS, Android )
Network interface	1*RJ45 10/100M adaptive Ethernet port; support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP etc.
Reliability	Comprehensive lightning protection, 7 * 24 hours 65 °C high temperature stable and reliable testing
Intelligence analysis	Alarm line, alarm region, goods stranded, video block, fuzzy detection, scene change
Other function	Support WEB,OSD live video transmission, motion detect and IO alarm, front-end storage/playback/download, and center reminder and image linkage, support JPEG capture united remote client monitoring software, MYEYE perfect SDK;
Power	DC12V/2A input, power consumption:≤3W
Ingression Protection	IP66 Waterproof Outdoor
material	Metal
Working Temperature	-20°~65°



www.iid2secure.nl  
Extra Benefits, Less Price  
Finestrat,19, 03530 La Nucia, Alicante, Spain  
© IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands  
Support@iid2secure.nl  
+31614762425  
Data Subject to change without notice