

# IID-XVR08P



## Key Feature:

- Support VGA, HDMI full HD output simultaneously
- Support ONVIF; access third party
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions
- Support web, CMS, center platform management software MYEYE, provide SDK development
- Support various mobile monitoring (iPhone, Android)
- Remote Access, With DNS (ARSP), easy to monitor remotely
- Support UTC, control signal& video stream transmits through one single coaxial
- Support XVI/AHD/TVI/CVI/CVBS/IP Six signals

Model		IID-XVR08P	
System	Main chip	Hi3521A	
	OS	LINUX	
	System Resources	Multi-channel Realtime recording, Multi-channel playback, Multi-channel network operation, USB Backup	
Interface	Operation menu	16-bit true color graphical menu interface, mouse operation supported	
	Display	1/4/8/9 display (take the pure coaxial input mode as an example)	
Video	Format	H.264	
	Output	VGA,HDMI;HD	
	Preview	8*1080P@25fps	
	Recode	8*1080P@12fps	
	Decord	4*1080P@12fps	
	Multi-mode Input	Analog	: 8*1080P; 8*1080N
		Hybrid	: 4*1080P (Analog) +4*1080P (IP) ;
Network		:8*1080P+8*960P;	
Network		:4*3M ;4*5M	
Motion Detect	Each view window can set 192 (16*12) detection area,can set multi-level sensitivity (only for local channel)		
Audio	Audio	G.711A	
	Intercom	Support	



www.iid2secure.nl  
Extra Benefits, Less Price  
Finestrat,19, 03530 La Nucia, Alicante, Spain  
© IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands  
Support@iid2secure.nl  
+31614762425  
Data Subject to change without notice



Recorind and Playback	Recording mode	Manual、Alarm、Motion Detect、Timer
	Local playback	8 Channel (when Analog mode)
	Video search	Time, Date,Event,Channel search
Storage and Backup	Storage	Local HDD, Network
	Backup	Network back, USB Drive, HDD
Port	Video Input	8 * BNC
	Video Output	1 * VGA, 1 * HDMI
	Spot Monitor	no
	Audio Input	8 * RCA
	Audio Output	1 * RCA
	Alarm Input	4 channel
	Alarm Output	1 channel
	Network port	RJ45 10M/100M
	PTZ Control	1 * RS485 Support multipal PTZ Contract
	USB port	2 * USB Port
	HDD Port	1 * SATA hdd ports (up to 6T for each one)
	Wireless	3G、WIFI(can be USB WIFI Dongle)
Others	Power	1*HDD: 12V/2A 2*HDD: 12V/5A
	Power consumption	Less than 15W (no HDD)
	Working temperature	0 —+55
	Working humidity	10%—90%
	Atmospheric pressure	86kpa—106kpa



[www.iid2secure.nl](http://www.iid2secure.nl)  
 Extra Benefits, Less Price  
 Finestrat,19, 03530 La Nucia, Alicante, Spain  
 © IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands  
 Support@iid2secure.nl  
 +31614762425  
 Data Subject to change without notice