

# JSC-15T Surface Mount Ceiling Speaker

#### **Features**

- Built-in 100v/70v transformer
- Surface Mount ceiling type loudspeaker
- 4" speaker unit
- Power taps 3W @100V
- ABS grille, ABS baffle and ABS back cover

#### **Description**

The JSC-15T is a ceiling speaker built-in 70v/100v transformer. The 70v/100v transformer technique reduces line losses on longer distance and allows easy parallel connection of multiple loudspeakers.

The built-in 4" speaker driver is designed of wide frequency response 110-16kHz, power output is 3 watts. The ABS grille, ABS baffle and ABS back cover are in attractive white color.



The surface mount type is designed for some special application where cutting hole in roof is impossible, so the speaker needs to be directly mounted to the surface of the roof.

It is ideal choice for industrial and commercial applications in hotel, school, office and factory where background music and paging is needed.

#### **Specification**

Model	JSC-15T
Power Taps @100V	3W
Power Taps @70V	1.5W
Impedance	Black: Com Red: 3.3KΩ
SPL(1W/1M)	92dB
Max.SPL (Rated W/1M)	97dB
Frequency Response (-10dB)	110-16KHz
Finish	Baffle: ABS, White Grille: ABSI, White
Speaker Driver	4" ×1
Dimensions	180×70mm
Weight	0.6Kg
Mounting	Fixed by screw



# JSC-15T Surface Mount Ceiling Speaker

### Appearance:



## Frequency Response:

