



FRONT PANEL



REAR PANEL

KB-D12M

16-CHANNEL MONITOR PANEL

Monitor up to 16 speaker channels audibly by using the built-in loudspeaker. Graphic LCD level meter visually indicates the channel's signal level.

Compatible equipment: KB-D100, KB-D13A, KB-D13B

FEATURES

- 16 monitor channels, independent volume for each monitor channel
- LCD display current monitor channel and the correspondent monitor volume
- Select monitor channel and control monitor volume through buttons
- 7 grades (0-6) volume control for each channel
- Automatic cycle monitor function, set cycle time through remote control unit
- Have functions of remotely read the present monitor channel and volume, remote turning on/off, remote monitor channel selection, remote volume control, remote cycle monitor control and remote time-set of automatic cycle monitor
- Short circuit signal activation
- Apply switch of address setting, use decimal system to set the local address

SPECIFICATIONS

Input(MIC)	70/100V, audio signal
Monitor speaker	32 steps, digital control
Indicators	Built in stereo hifi full range speaker, power>500mw
Volume ControlProtection	AC Fuse × 0.5A × 1
Power Requirements	AC 220V ± 10% 50-60Hz
Power Consumption	10~15W
Dimensions	89(H) × 483(W) × 350(D)mm
Net Weight	5.1Kg
Gross Weight	6.3Kg

Ordering Information

KB-D12M

16-Channel Monitor Panel