

Audio Sources

KB-PAM120/ 240 / 360

These commercial-grade power amplifiers efficiently deliver up to 120-360 watts of clean, reliable audio for the most demanding public address and voice alarm applications.

Rugged and over-built to give years of dependable service, they are equipped with massive power transformers, extensive heat-sinking and fan cooling, protective circuits such as over-temperature, short circuit, RFI and soft start.

100V, 70V and 4 Ohms transformer-isolated speaker outputs
 Balanced XLR input with XLR parallel link-out connector
 400Hz high pass filter
 Ground Selector Switch:
 Frame/float Adjustable input gain from -12dB to 0dB



Specification	KB-PAM120	KB-PAM240	KB-PAM360
Rated Power Output	120W	240W	360W
Gain Control	-12 dB to 0		
Speaker Output	41 ohms 70V 83 ohms 100V	21 ohms 70V 41 ohms 100V	13.6 ohms 70V 27.8 ohms 100V
Frequency Response	80Hz~20kHz		
THD	<1.0% at 1kHz (1/2 Rated output)		
S/N Ratio	>90 dB		
Controls	Volume control and power switch		
Cooling	Internal 12VDC fan, extensive heat sinking		
Power Consumption	485W	500W	1400W
Power Requirements	110V/60Hz or 230V/50Hz AC, 24V DC		
Dimensions	89(H) x 482(W) x 377(D) mm		
Built-in Dimensions	2 U rack 19 inch		
Carton Dimensions	185(H) x 520(W) x 435(D) m		
Net Weight	13kg	17kg	20kg
Color	Black		