

KH2008B Intelligent GSM/PSTN Alarm system



Wireless Wired Long Distance Alarm System:

- 1) The host with keyboard and LCD display, it is convenient to operate the host program.
- 2) The host with intelligent voice features.
- 3) The host with 16wired zone and 100 wireless zone, wired and wireless use the same zone number
- 4) With outstanding password, engine password, user password monitor, convenient to user operation and engine monitor.
- 5) Connected with Contact ID.
- 6) It can store 6group telephone number
- 7) With the function which can get the first line when alarm and send the alarm system out.(8) When the telephone line is cut or short circuit, it will alarm.

9) It can dial the telephone number contact with the host through remote phone and cell phone, used in long distance monitor, arm, disarm and field alarm.

10) Wireless detector and remote control are automatic code

11) 16 wired zone can be set arbitrary as: N.C, N.O, end line resistance, in order to connect with any wired detector.

12) It can set up 2 group regular time, auto arm and disarm to different zone.

13) It can set freely alarm delay time(00--99second) and arm delay time (0000--0255second)

14) Checking arm, disarm, alarm issue, etc.

15) The host adopts AC220V, DC12V/7AH dual power supply. Usually, recharge for battery, when AC power cut, it will auto-change into battery supply. (it can be able to work more than 24-hour standby). When the battery is lower, it will alarm, the discharge limit protection circuit design, so as to avoid damage due to discharge the battery.