



# SYSTEM DETECTORS NB-983 - CONVENTIONAL GAS & CO DETECTOR

The NB-983 series of conventional Gas and CO detectors were engineered based on the Japanese Figaro sensing component with 5-year warranty on the component. They also come with a 70-dB self-sounder built in. They can be calibrated into either UL or EN-54 standards. A super quality detector for the flammable and toxic gas application.

## The Range Includes

- NB-983 NG** Natural Gas detector with Relay Output
- NB-983 LP** Propane Gas detector with Relay Output (LPG)
- NB-983 CO** Carbon Monoxide detector with Relay Output


## Product Features

- 4 wire models
- FIGARO semiconductor sensor heads used for gas detection
- Loud 70 dB sound signal at alarm mode
- Advanced detection and discrimination algorithms
- Easy installation and maintenance
- Sleek low-profile housing design
- Durable sensor head, no need for replacement
- SMD circuit board design- quality and reliability guaranteed
- Magnet test feature
- Five-year limited warranty

## Options

- N/C (normal/close)-N/O (normal/open) selectable relay output
- Explosion proof versions

## Sensor Specification



Model	Type of gas Sensed	Voltage DC	Power Consumption	operating Temperature	Sensitivity	Output Voltage	Start up Current (MA)	Base model
<b>NB-983 NG</b>	Natural(NPG)	12/24VDC	2W	-10°C~50°C	Per UL 1484 or EN 50194	12/24	Relay Output	P/N774912
<b>NB-983 LP</b>	Propane(LPG)	12/24VDC	2W	-10°C~50°C	Per UL 1484 or EN 50194	12/24	Relay Output	P/N774912
<b>NB-983 CO</b>	CO	12/24VDC	2W	-10°C~50°C	Per UL 2034 or EN 50291		Relay Output	P/N774912

LICHFIELD FIRE AND SAFETY EQUIPMENT CO. LTD.

2nd Floor | Suite 4 | Saturn Centre | Spring Road | Ettingshall | Wolverhampton | WV4 6JX | United Kingdom  
Tel: +44 (0) 870 066 4401 | Fax: + 44 (0) 870 066 4402 | E-mail: info@lifeco-uk.com | www.lifeco-uk.com