

# Model: S6-RX



## Metal Wiegand Reader Access RFID Card Reader(E/H/Mifare)

- > Metal Case, anti-vandal
- > Waterproof conforms to IP66
- > Wiegand 26~37 bits output (default: 26bits)
- > Card type: Hid card, EM card & Mifare card
- > Reading range: 3~8cm
- > External LED Control & External Buzzer Control

**Brand:** S4A

**Item NO.:** S6-RX



## Metal Wiegand Reader Access RFID Card reader(E/H/Mifare)

**Model No.:** S6-RX 125KHz&13.56MHz

The S6-RX reader is an advanced 125KHz & 13.56MHz technology proximity reader.

Because of metal case anti-vandal and waterproof, it can be mounted either indoor or outdoor in a harsh environment.

- > Metal Case, anti-vandal
- > Waterproof conforms to IP66
- > Wiegand 26~37 bits output (default: 26bits)
- > Card type: Hid card, EM card & Mifare card
- > Reading range: 3~8cm
- > External LED Control & External Buzzer Control

|                       |  |
|-----------------------|--|
| Operating Voltage     | 9~24V DC                                       |
| Frequency             | 125KHz & 13.56MHz                              |
| Card Type             | 125KHz - EM & Hid Card                         |
|                       | 13.56MHz - Mifare Card (ISO 14443A Compatible) |
| Reading Distance      | 3~8 CM   |
| Output Format         | Wiegand 26 bits                                |
|                       | (26~37 bits available upon request)            |
| Operating Temperature | -40°C ~ 60°C (-40°F ~ 140°F)                   |
| Standby Current       | < 25mA   |
| Operating Humidity    | 10%~98% RH                                     |
| Index of Protection   | IP66   |
| Dimensions            | L103 x W48 x H19 (mm)                          |



Data 0   
Data 1 

Wiegand 26~37bits(default 26bits)



Metal Case, Anti-vandal



Card Type: EM+HID+Mifare



50cm cable  
(Standard)



RJ45  
(optional)



Terminal Blocks  
(Optional)

3 Kinds of Interface