

Bluetooth Single door Access Controller

Sboard-BT Access control

- 1: User Capacity: 1000 users
- 2: Working Voltage: 9-24V
- 3: Relay: NO NC COM
- 4: Support Wiegand 26-37bits output
- 5: APP download available for both Android and IOS
Version by searching Ksmart



Technical Specification:

User Capacity	1,000
Operating Voltage	9~24V DC
Idle Current	< 20mA
Relay	One (NO, NC, Common)
Adjustable Relay Output Time	0~99 Seconds (5 seconds default)
Lock Output Load	2 Amp Maximum
Wiegand Interface	
Input	Wiegand 26~37 bits
Output	Wiegand 26~37 bits (for user transfer)
Environment	Indoor
Operating Humidity	0 ~ 90%RH
Physical	ABS Shell
Colour	Black
Dimensions	6.5L x 5.4W x 1.9H (cm)
Unit Weight	40g
Shipping Weight	100g

- > Compatible with all Bluetooth-enabled mobile phones (version: 4.0 above) to access the door
- > APP support Android 4.3 and IOS7.0 above
- > 1,000 users,user data can be transferred
- > Multi access modes: Card, Card or PIN, Card with PIN and multi Cards/PINs
- > Can connect with any reader with Wiegand 26~37 bits output
- > Can connect with any keypad reader with 4bits, 8bits (ASCII), or 10bits Virtual number output



Sboard-BT is a single door controller with embedded Bluetooth module which can access doors by smart phone who is compatible with both Android and iOS . It also supports to connect with any wiegand reader with 26~37 bits output.