



TTE GPRS Standard

Universal GPRS Communication Module

Description

TTE GPRS Standard is an universal communication module. It is used for connection to intruder alarm panels or as a stand-alone device. The device is connected to Teletek Electronics panels via serial connection or to other panels via its 6 inputs/outputs. TTE GPRS Standard is used to send alarm messages to monitoring center or end-user. The module is mounted in small plastic box suitable for wall mounting.

TTE GPRS Standard can also be used for remote management, programming and monitoring of the security system together with Teletek Electronics panel and the AJAX SP PRO software application. The module has home automation function.

Technical Specifications

- Power supply 9-30 V DC
- Current Consumption:
 - - Normal operation mode (Standby) . . . 50 mA
 - - Signal transmitting (GSM) max 1.6 A
- Programmable inputs/outputs 6, 100 mA, OC type
- Phone numbers for events notification 6
- SMS messages up to 12
- Input filtration time 0.5 sec
- Input for AC monitoring 9-35 V AC
- Operating frequency 850/900/1800/1900 MHz
- Antenna connector (SMA) 50 Ohm
- Encryption AES 128 bits



Functional Specifications

- SMS notifications for test, main and back-up power supply;
- Indication for the network status, trouble with the connection to the control panel, etc.;
- Internet remote programming and control through AJAX SP PRO/MobileTTE;
- Micro USB port for module configuration;
- SIM interface;
- 2GB micro SD card for voice messages;
- Serial connection to ECLIPSE series control panels;
- Reset jumper;
- Suitable for home automation control.

Packing Information

- **Single packing box** - 1 unit TTE GPRS Standard (PCB), dimensions 105 x 108 x 46 mm
- **Master box** - 90 units TTE GPRS Standard, dimensions 560 x 362 x 320 mm

Compatible Product Range

- **Eclipse series** - Alarm control panels 8/ 16/ 32 zones
- **SB-U** - small universal box
- **Other intruder alarm systems**

Contact Information