

TZ-206W AS

COLUMN SPEAKER



The TZ Series Column Speakers are highly efficient compact speakers that deliver excellent sound performance in medium sized venues such as houses of worship, gymnasiums, auditoriums and more.

Key features

- Column Speaker is suitably designed for in-door use and/or outdoor use.
- Efficient for use in a spacious room.
- The speaker unit is designed to reproduce sound with good clarity and high input power capacity.
- The plastic column speaker comes with speaker bracket as accessories.
- The speaker bracket offers better installation flexibility.

1


Specifications

Sealed Type
20 W
100 V line: 500 Ω (20 W), 1 k Ω (10 W), 2 k Ω (5 W), 4 k Ω (2.5 W) 70 V line: 500 Ω (10 W), 1 k Ω (5 W), 2 k Ω (2.5 W), 4 k Ω (1.3 W)
90 dB (1 W, 1 m)
150 Hz - 16,000 Hz
10 cm (4") cone-type x 2
Push-In terminals
Enclosure: HIPS, white Punched Net: Surface-tread steel plate, white, paint Speaker Bracket: Aluminum die-cast, white, paint Joint Bracket, Wall Bracket: Steel plate, t1.6 mm, white, paint
135 (W) x 250 (H) x 128 (D) mm (5.31" x 9.84" x 5.04")
1.9 kg (4.18 lbs.) unit only
Speaker Bracket x 1, Joint Bracket x 1, Wall Bracket x 1, Fixing Bolt (M5 x 60) x 1, Hexagon Bolt (M6 x 12) (with plain washer and spring washer) x 2, Machine Screw (M5 x 20) (with plain washer and spring washer) x 2, Hexagon Bolt (M8 x 15) x 1
Speaker Stand: ST-16A



Dimensions





M8 (depth 13(0.51")

(for stand mounting)

Bottom View

2-M5 (depth 10(0.39")

(for bracket mounting)

30 (1.18")

Side View

Rear View Rotary Switch

UNIT: mm