



XVR32A32D4K8S



Key Features

- Support AHD/CVI/TVI/IP/Analog Camera Input
- Up to HD 5MP and IP 8MP Resolution Recording
- Support HD Output, VGA and CVBS Video Output
- Support Max. 32CH HD or 32CH IP Camera Input
- Support 8 SATA up to 64TB and 1 E-SATA up to 8TB Capacity



www.iid2secure.nl
Extra Benefits, Less Price
Finestrat,19, 03530 La Nucia, Alicante, Spain
© IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands
Support@iid2secure.nl
+31614762425
Data Subject to change without notice



Specification

Model NO.	XVR32A32D4K8S
System	
Main Processor	HI3531D
Operating System	Embedded LINUX
Video	
Input	Normal Mode: Analog: 32*(AHD/TVI/CVI:8M; TVI/AHD: 5M; AHD/TVI/CVI: 4M; AHD/TVI: 3M; AHD/TVI/CVI: 1080P/720P; Analog: 960H) Lite Mode: Analog: 32*(AHD/TVI/CVI: 1080P/720P; Analog: 960H) Analog + Network: 30*Analog+2*network (Max 8MP), 28*Analog+4*network(Max 8MP), 26*Analog+6*network(Max 8MP), 24*Analog+8*network(Max 8MP), 22*Analog+10*network(Max 8MP), 20*Analog+12*network(Max 8MP), 18*Analog+14*network(Max 8MP), 16*Analog+16*network(Max 8MP), 14*Analog+18*network(Max 8MP), 12*Analog+20*network(Max 8MP), 10*Analog+22*network(Max 8MP), 8*Analog+24*network(Max 8MP), 6*Analog+26*network(Max 8MP), 4*Analog+28*network(Max 8MP), 2*Analog+30*network(Max 8MP) Network: 32*network(Max 8MP)(Total incoming bandwidth ≤160M)
Input	23CH BNC
Signal Type	Analog/AHD/CVI/TVI/Network
Output	1 HD, 1 VGA, 1 CVBS
Audio	
Input	12 Channel, RCA
Two-way Audio	NO
Output	1 Channel, RCA
Alarm	
Sensor Input	16 Channel
Output	4 Channel
Motion Detection	32 Channel
Trigger Events	Recording, Email, Screen tips, Buzzer, Push notifications(motion detection)
Email Alarm	Send Image to The Designated E-mail
PTZ	
Interface	RS485
Protocol	Pelco-D, Pelco-P
Baud Rate	110~921600
Address	0~255
Display	
VGA	Resolution: 1920 × 1080P /60Hz, 1280 × 1024 /60Hz
HD Output	Resolution: 3840×2160/30Hz, 1920 × 1080P /60Hz, 1280 × 1024 /60Hz
Display Split	36 Channel/25 Channel/16 Channel/9 Channel/8 Channel/4 Channel / 1Channel
Privacy Masking	3 Rectangular Zones (Each camera)
OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording
Recording	
Video Compression	H.265/H.265+/H.264/H.264+
Audio Compression	G.711U
Resolution	5MP(2592×1944),8MP_LITE(1920×2160),5MP_HALF(1296×1944),4MP(2560×1440),4MP_HALF(1280×1440),3MP(2048×1536),1080P(1920×1080),720P(1280×720),960H(P:960×576/N:960×480)
Video Quality	Worst/Worse/Ordinary/Well/Best



www.iid2secure.nl
 Extra Benefits, Less Price
 Finestrat,19, 03530 La Nucia, Alicante, Spain
 © IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands
 Support@iid2secure.nl
 +31614762425
 Data Subject to change without notice



Record Rate	Normal Mode: Analog: PAL: 8MP_LITE(1920x2160 32*8fps), 5MP(2592x1944 32*6fps), 5MP_LITE(1296x1944 32*10fps), 4MP(2560x1440 32*8fps), 4MP_LITE(1280x1440 32*15fps), 3MP(2048x1536 32*9fps), 1080P(1920x1080 32*15fps), 720P(1280x720 32*25fps), 960H(960x576 32*25fps) NTSC: 8MP_LITE(1920x2160 32*8fps), 5MP(2592x1944 32*6fps), 5MP_LITE(1296x1944 32*10fps), 4MP(2560x1440 32*8fps), 4MP_LITE(1280x1440 32*15fps), 3MP(2048x1536 32*9fps), 1080P(1920x1080 32*15fps), 720P(1280x720 32*30fps), 960H(960x480 32*30fps) Lite Mode: Analog: Half 1080P(960x1080 32*25fps), 720P(1280x720 32*25fps), 960H(P:960x576 32*25fps/N:960x480 32*30fps) Pure IP(H.265): PAL: 4k@17x25fps, 5MP@26x25fps, 4MP@32x25fps, 3MP@32x25fps, 1080P@32x25fps, 960P@32x25fps, 720P@32x25fps, D1@32x25fps NTSC: 4k@17x30fps, 5MP@26x30fps, 4MP@32x30fps, 3MP@32x30fps, 1080P@32x30fps, 960P@32x30fps, 720P@32x30fps, D1@32x30fps
Record Mode	Manual\Timer\Motion Detection
Playback & Backup	
Decode Capability	9CH 720P@30fps
Sync Playback	Pure Analog: 16CH 8MP_LITE@8fps, 16CH 5M@6fps, 16CH 5MP_LITE@10fps, 16CH 4M@8fps, 16CH 4MP_LITE@15fps, 16CH 3M@9fps, 16CH 1080p@15fps, 16CH 1080N@25fps Mix Mode: 2CH 4K@30fps, 2CH 5M@30fps, 2CH 4M@30fps, 3CH 3M@30fps, 8CH 1080P@30fps, 8CH 960P@30fps, 8CH 720P@30fps Pure IPC: 2CH 4K@30fps, 4CH 5M@30fps, 4CH 4M@30fps, 5CH 3M@30fps, 9CH 1080P@30fps, 9CH 960P@30fps, 9CH 720P@30fps
Remote Playback	4 Channel / 1Channel
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast play, Rewind, Digital Zoom, Full screen
Smart Phone Playback	4 Channel
Backup Mode	USB Device(with format FAT 32)/Network/FTP
Network	
Interface	1 RJ45 10M/100/1000M Adaptive Ethernet Interface
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP
DDNS	Dyndns, change ip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE
Web Browser	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
CMS Software	Support Windows 7/ Windows 8/Windows 10
Extra Stream	CIF(1~30fps)
Smart Phone	iPhone, iPad, Android ,Android pad
Hard Disk Driver	
Interface Type	8 SATA Interface
Capacity	8 SATA Hard Disk (3.5" SATA, Up to 64TB) + 1 E-SATA Interface (Up to 8TB)
General	
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek
UTC Control	YES
USB Interface	2 USB 2.0 Interfaces
Power consumption	AC 115~230v ≤35W (Without HDD)
Working Environment	-10~55°C/10~90%
Dimension (WxDxH)	440*450*95(mm)
Weight	9.8kg (Without HDD)



www.iid2secure.nl
 Extra Benefits, Less Price
 Finestrat, 19, 03530 La Nucia, Alicante, Spain
 © IID Secure Tech S.L.U. 2019

Heemstedestraat 16 Amsterdam, Netherlands
 Support@iid2secure.nl
 +31614762425
 Data Subject to change without notice

Dimensions

